

## Wencon Aggregate & Filler

### **Wencon Aggregate**

#### General Description

Wencon Aggregate are silica carbide based fine granulates, which are used for both the Wencon Non-Slip surfacing and the Wencon Wear Resistant Coating (see special instructions for use).

Wencon Aggregate is supplied in sets containing 1,5 kg.

### **Wencon Mixed Filler**

#### General Description

Wencon Mixed Filler is a custom made filler to be mixed with epoxy products.

For jobs, where there is a demand for an extra wear protection and if you need to improve durability,  
For extra abrasion resistance, mix Wencon Mixed Filler with Wencon Cream, Wencon Rapid or Wencon Coating.

Mix up to 1 tin (500 ml) Wencon Mixed Filler with 1 kg Wencon Cream, Rapid or Coating.

Before applying the mixture, apply a thin layer of Wencon Cream ,Wencon Rapid or Wencon Coating on the surface (without Wencon Mixed filler). This will increase the adhesion.

# Wencon Aggregate & Filler

## Wencon Aggregate

### General Description

Wencon Aggregate er granulater baseret på silicium carbider. Wencon Aggregate bruges til skridsikre belægninger (se vejledning 111 i håndbogen).

Wencon Aggregate leveres i sæt med 1,5 kg.

## Wencon Mixed Filler

### General Description

Wencon Mixed Filler er et hårdt granulat som tilsættes for at gøre produkterne mere slidstærke. Bruges til opgaver, hvor der er ønske om ekstra beskyttelse mod slid og til opgaver hvor der er brug for at forbedre holdbarheden.

For ekstra slidstyrke bland Wencon Mixed Filler med Wencon epoxy produkt.

Bland op til 500ml Wencon Mixed Filler med 1 kg Wencon produkt

For øget vedhæftning, påføres et tyndt lag Wencon Cream

,Wencon Rapid eller Wencon Coating inden der blandes Mixed Filler i.