

# Wencon Reinforcement Tape

## Wencon Reinforcement Tape

### General Description

Wencon Reinforcement Tape is a fibre tape used for reinforcing the Wencon repair. e.g. pipe repairs and repairs of cracks or holes in engine blocks, oil sumps, etc. After mixing e.g. the Wencon Cream, cut off a length of reinforcement tape. Place it on the mixing board and apply a 2-5 mm thick layer of Wencon Cream on top, using the mixing knife.

Next wrap the impregnated Wencon Reinforcement Tape around the pipe having the Wencon Cream on the inner side. The length of the tape should enable it to go 3-4 times around the pipe.

Wencon Reinforcement Tape is supplied in following units:

Wencon Reinforcement Tape 0,05 x 10 m (400 inch)

Wencon Reinforcement Tape 0,10 x 20 m (800 inch)

# Wencon Reinforcement Tape

## Wencon Reinforcement Tape General beskrivelse

Wencon Reinforcement Tape er et fibertape, der bruges til at forstærke Wencon reparationen. f.eks. rørreparationer og reparation af revner eller huller i motorblokke, oliebrønde etc. Efter blanding af eksempelvis Wencon Cream, afskæres en længde af Reinforcement Tape. Placer det på blandebordet og anbring et 2-5 millimeter tykt lag Wencon Cream ovenpå ved hjælp af blandedkniven.

Pres så det belagte tape rundt om røret med Wencon Cream på inder-siden.

Længden på tapen skal kunne gå 3-4 rundt om røret.

Wencon Reinforcement Tape leveres i flg.

Ruller á 5cm x 10m

Ruller á 10cm x 20m