

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Wencon Hi-Temp Green - Component A (185000060A)  
PR-number (Danish): 1593670

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Solventfree two component coating based on epoxy

#### Relevant identified uses

In compliance with the conditions described in the annex to this safety data sheet. See section 16 for a comprehensive list of uses, for which an exposure scenarion is provided as an annex.

#### Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process categories [PROC]

PROC 10 - Roller application or brushing

PROC 19 - Manual activities involving hand contact

PROC 21 - Low energy manipulation of substances bound in materials and/or articles

PROC 24 - High (mechanical) energy work-up of substances bound in/on materials and/or articles

#### Environmental release categories [ERC]

ERC 8c - Widespread use leading to inclusion into/onto article (indoor)

ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

ERC 10a - Widespread use of articles with low release (outdoor)

ERC 11a - Widespread use of articles with low release (indoor)

#### Article categories [AC]

AC 7 - Metal articles

#### Uses advised against

Do not use for private purposes (household).

#### Remark

The product is intended for professional use.

### 1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer) : Wencon ApS  
Street : Jyllandsvej 15  
Postal code/city : DK-5400 BOGENSE  
Telephone : +45 6481 1010  
Information contact : wencon@wencon.com

### 1.4 Emergency telephone number

+44 870 600 62 66 (UK National Poisons Emergency Number)  
European emergency number: 112. Denmark: (Giftlinjen +45 82 12 12 12), only for the purpose of informing medical personnel in cases of acute intoxications.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

### 2.2 Label elements

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

### Hazard pictograms



Environment (GHS09) - Exclamation mark (GHS07)

### Signal word

Warning

### Hazard components for labelling

BIS-[4-(2,3-EPOXIPROPONI)PHENYL]PROPANE ; CAS No. : 1675-54-3  
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER ; CAS No. : 28064-14-4  
BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW ≤ 700 ; CAS No. : 9003-36-5  
REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9  
PHENOL, METHYL STYRENATED ; CAS No. : 68512-30-1  
2,3-EPOXYPROPYL NEODECANOATE ; CAS No. : 26761-45-5

### Hazard statements

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Special rules for supplemental label elements for certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

## 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

QUARTZ (SiO<sub>2</sub>) ; REACH No. : Annex V ; EC No. : 238-878-4; CAS No. : 14808-60-7

Weight fraction : ≥ 25 - < 50 %

Classification 1272/2008 [CLP] : STOT RE 2 ; H373

BIS-[4-(2,3-EPOXIPROPONI)PHENYL]PROPANE ; REACH No. : 01-2119456619-26 ; EC No. : 216-823-5; CAS No. : 1675-54-3

Weight fraction : ≥ 10 - < 25 %

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER ; EC No. : 608-164-0; CAS No. : 28064-14-4

Weight fraction : ≥ 10 - < 25 %

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW ≤ 700 ; REACH No. : 01-211-454392-40 ; EC No. : 500-006-8;

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

CAS No. : 9003-36-5  
Weight fraction :  $\geq 10 - < 25$  %  
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; REACH No. : 01-2119463471-41 ;  
EC No. : 618-939-5 ; CAS No. : 933999-84-9  
Weight fraction :  $\geq 2,5 - < 10$  %  
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 3 ; H412

PHENOL, METHYL STYRENATED ; REACH No. : 01-2119555274-38 ; EC No. : 270-966-8 ; CAS No. : 68512-30-1  
Weight fraction :  $< 0,5$  %  
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Chronic 3 ; H412  
2,3-EPOXYPROPYL NEODECANOATE ; REACH No. : 01-211943157-33 ; EC No. : 247-979-2 ; CAS No. : 26761-45-5  
Weight fraction :  $< 0,5$  %  
Classification 1272/2008 [CLP] : Muta. 2 ; H341 Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

#### Additional information

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. If unconscious place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label.

#### In case of skin contact

In case of skin reactions, consult a physician. Immediately remove any contaminated clothing, shoes or stockings. After contact with skin, wash immediately with plenty of water and soap. Do not use force or solvents to remove product incrustations from affected skin areas. Do not let product dry on skin.

#### After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

### 4.2 Most important symptoms and effects, both acute and delayed

Causes damage to organs through prolonged or repeated exposure.

#### Effects

After eye contact  
Irritating to eyes.

In case of skin contact  
Irritating to skin. May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam

#### Unsuitable extinguishing media

Water spray jet

### 5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Use suitable breathing apparatus.

#### Hazardous combustion products

Carbon monoxide

### 5.3 Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

### 5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Do not breathe gas/fumes/vapour/spray. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Use personal protection equipment. See protective measures under point 7 and 8.

#### For emergency responders

Do not breathe gas/fumes/vapour/spray. Use personal protection equipment. See protective measures under point 7 and 8.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Ensure waste is collected and contained.

### 6.3 Methods and material for containment and cleaning up

#### For containment

Ensure waste is collected and contained.

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation. Clean with detergents. Avoid solvent cleaners. Treat the recovered material as prescribed in the section on waste disposal.

### 6.4 Reference to other sections

None

## SECTION 7: Handling and storage



### 7.1 Precautions for safe handling

#### Protective measures

Persons with a history of skin sensitisation problems should not be employed in any process in which this product

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

is used. It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). Never use pressure to empty container. Use only in well-ventilated areas.

**Measures to prevent fire**

Keep away from sources of ignition - No smoking.

**Environmental precautions**

Do not allow to enter into surface water or drains.

**7.2 Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Only use containers specifically approved for the substance/product. Keep/Store only in original container. Keep container tightly closed.

**Hints on joint storage**

Keep away from:

**Further information on storage conditions**

Keep only in the original container in a cool, well-ventilated place. Store in a place accessible by authorized persons only. Handle and open container with care.

**7.3 Specific end use(s)**

Observe instructions for use. The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

None

**8.2 Exposure controls**

**Personal protection equipment**



**Eye/face protection**

**Suitable eye protection**

Eye glasses with side protection

**Skin protection**

**Hand protection**

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Wear cotton undermitten if possible.

**Suitable gloves type** : Disposable gloves.

**Suitable material** : NBR (Nitrile rubber)

**Required properties** : liquid-tight.

**Breakthrough time (maximum wearing time)** : > 60 minutes

**Thickness of the glove material** : > 0.5 mm

**Recommended glove articles** : EN 374

**Additional hand protection measures** : Do not wear gloves near rotary machines and tools. Check leak tightness/impermeability prior to use. Wear cotton undermitten if possible. Use gloves only once. Take recovery periods for skin regeneration.

**Remark** : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Observe the wear time limits as specified by the manufacturer. Breakthrough times and swelling

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

properties of the material must be taken into consideration. In the case of wanting to use the gloves again, clean them before taking off and air them well. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Barrier creams are not substitutes for body protection.

#### Body protection

Remark : Body protection: not required.

#### Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values  
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Filtering device (DIN EN 147) Full-/half-/quarter-face masks (DIN EN 136/140) Filtering Half-face mask (DIN EN 149) Particle filter device (DIN EN 143).  
Filtering device (full mask or mouthpiece) with filter: A P

#### Additional measures for respiratory protection

Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m<sup>3</sup> (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m<sup>3</sup> (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m<sup>3</sup> (1.0 % by vol.) Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo. Full-face mask or mouthpiece with particulate filter: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 15 times the exposure limit. P3 filter: up to a max. of

#### Remark

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

#### General information

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Immediately remove any contaminated clothing, shoes or stockings.

#### Other protection measures

##### Product related measures to prevent exposure

Further information: see technical data sheet.

##### Instructional measures to prevent exposure

Further information: see technical data sheet.

##### Organisational measures to prevent exposure

Further information: see technical data sheet.

##### Technical measures to prevent exposure

Technical measures and the application of suitable work processes have priority over personal protection equipment. See section 7. No additional measures necessary.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : Paste

#### Appearance

Colour : yellow

#### Odour

characteristic

#### Safety characteristics

Melting point/freezing point : not applicable

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

Initial boiling point and boiling range :	( 1013 hPa )		No data available
Decomposition temperature :			No data available
Flash point :		>	150 °C DIN 53213-1
Auto-ignition temperature :			No data available
Evaporation rate :		<	1
Flammable gases :			Not applicable.
Flammable solids :			Not applicable.
Oxidising properties.			No data available.
Lower explosion limit :			No data available
Upper explosion limit :			No data available
Explosive properties :			No data available.
Vapour pressure :	( 50 °C )	<	1000 hPa
Relative vapour density :			No data available
Relative density :	( 20 °C )	approx.	1,63 g/cm <sup>3</sup> DIN 53217
Water solubility :	( 20 °C )		practically insoluble
Partition coefficient n-octanol/water :			No data available
pH :			No data available
Viscosity :	( 20 °C )		not applicable
Cinematic viscosity :	( 40 °C )		No data available
Odour threshold :			No data available

## 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4 Conditions to avoid

Ignition hazard.

### 10.5 Incompatible materials

Exothermic reaction with: Amines.

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

#### Acute toxicity

##### Acute oral toxicity

Parameter :	LC50 ( REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	30000 mg/kg
Parameter :	LD50 ( BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5 )

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

Exposure route : Oral  
Species : Rat  
Effective dose : > 2000 mg/kg  
Parameter : LC50 ( 1,6 HEXANDIOL DIGLYCIDYLETHER ; CAS No. : 16096-31-4 )  
Exposure route : Oral  
Species : Rat  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( N-METHYL-2-PYRROLIDONE ; CAS No. : 872-50-4 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 3600 mg/kg  
Parameter : LD50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 8500 mg/kg  
Parameter : LD50 ( MALEIC ANHYDRIDE ; CAS No. : 108-31-6 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 850 mg/kg  
Parameter : LD50 ( MALEIC ANHYDRIDE ; CAS No. : 108-31-6 )  
Exposure route : Oral  
Species : Mouse  
Effective dose : 60 mg/kg  
Parameter : LD50 ( 2-METHOXYPROPYL ACETATE ; CAS No. : 70657-70-4 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 8500 mg/kg  
Parameter : LD50 ( EPSILON-CAPROLACTAM ; CAS No. : 105-60-2 )  
Exposure route : Oral  
Species : Rat  
Effective dose : 1210 mg/kg

**Acute dermal toxicity**

Parameter : LC50 ( REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Parameter : LC50 ( 1,6 HEXANDIOL DIGLYCIDYLETHER ; CAS No. : 16096-31-4 )  
Exposure route : Dermal  
Species : Rat  
Effective dose : > 2000 mg/kg  
Parameter : LD50 ( EPSILON-CAPROLACTAM ; CAS No. : 105-60-2 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : 1438 mg/kg

**Acute inhalation toxicity**

Parameter : LC50 ( 2-METHOXY-1-METHYLETHYL ACETATE ; CAS No. : 108-65-6 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 35,7 mg/l



Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

Parameter : LC50 ( 2-METHOXYPROPYL ACETATE ; CAS No. : 70657-70-4 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 23,88 mg/l  
Parameter : LC50 ( EPSILON-CAPROLACTAM ; CAS No. : 105-60-2 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : 300 mg/m<sup>3</sup>

## Corrosion

### Skin corrosion/irritation

Irritating to skin.

### Serious eye damage/eye irritation

Irritating to eyes.

## Respiratory or skin sensitisation

EUH205 - Contains epoxy constituents. May produce an allergic reaction. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. Risk of serious damage to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

### Skin sensitisation

Parameter : Skin sensitisation ( BISPENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5 )  
Species : Guinea pig  
Effective dose : 50 %  
Result : Sensitising.  
Method : OECD 406

May cause an allergic skin reaction.

### Practical experience/human evidence

Causes skin irritation. Causes serious eye irritation.

## STOT-repeated exposure

### STOT RE 1 and 2

Causes damage to organs through prolonged or repeated exposure.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.

#### Aquatic toxicity

The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I. Toxic to aquatic life. May cause long lasting harmful effects to aquatic life.

#### Acute (short-term) fish toxicity

Parameter : Acute (short-term) fish toxicity ( BISPENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5 )  
Species : Acute (short-term) fish toxicity  
Effective dose : 2,54 mg/l  
Exposure time : 96 h  
Parameter : LC50 ( REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9 )  
Species : Leuciscus idus (golden orfe)  
Effective dose : 30 mg/l  
Exposure time : 96 h  
Parameter : EC50 ( REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9 )  
Species : Algae  
Effective dose : 23,1 mg/l  
Exposure time : 48 h

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

Parameter : EC50 ( REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9 )  
Species : Daphnia magna (Big water flea)  
Effective dose : 47 mg/l  
Exposure time : 48 h

#### Sediment toxicity

Toxicity to soil macroorganisms  
Acute earthworm toxicity  
Chronical earthworm toxicity (reproduction)  
Long-term toxicity of organisms living in the sediment

#### 12.2 Persistence and degradability

##### Abiotic degradation

###### Abiotic degradation (Water)

###### Hydrolysis

##### Biodegradation

Parameter : Biodegradation ( BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5 )  
Inoculum : Biodegradation  
Effective dose : 16 %  
Exposure time : 28  
Evaluation : Not readily biodegradable (according to OECD criteria)  
Method : OECD 301B

#### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

No information available.

#### 12.6 Other adverse effects

No information available.

#### 12.7 Additional ecotoxicological information

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3). Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Product/Packaging disposal

Do not allow to enter into surface water or drains.

##### Waste treatment options

###### Appropriate disposal / Product

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

###### Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of. Handle contaminated packages in the same way as the substance itself.

### SECTION 14: Transport information

#### 14.1 UN number

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

UN 3082

#### 14.2 UN proper shipping name

##### Land transport (ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ( BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE · PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER )

##### Sea transport (IMDG)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ( BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE · PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER · BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 )


##### Air transport (ICAO-TI / IATA-DGR)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ( BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE · PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER )

#### 14.3 Transport hazard class(es)


##### Land transport (ADR/RID)

Class(es) : 9  
Classification code : M6  
Hazard identification number (Kemler No.) : 90  
Tunnel restriction code : -  
Special provisions : LQ 5 l · E 1 · 375 · ADR : - (SP 375 <= 5 l/kg)  
Hazard label(s) :




##### Sea transport (IMDG)

Class(es) : 9  
EmS-No. : F-A / S-F  
Special provisions : LQ 5 l · E 1 · IMDG : - (SP 2.10.2.7 <= 5 l/kg)  
Hazard label(s) :



##### Air transport (ICAO-TI / IATA-DGR)

Class(es) : 9  
Special provisions : E 1 · A197 · IATA : - (SP A197 <= 5 l/kg)  
Hazard label(s) :



#### 14.4 Packing group

III

#### 14.5 Environmental hazards

Land transport (ADR/RID) : Yes  
Sea transport (IMDG) : Yes (P)  
Air transport (ICAO-TI / IATA-DGR) : Yes

#### 14.6 Special precautions for user

None

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

#### EU legislation

##### Authorisations and/or restrictions on use

##### Restrictions on use

Use restriction according to REACH annex XVII, no. : 3

##### National regulations

REACH-Regulation(1907/2006) Annex XVII [RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES] 3

Directive 2004/42/EC is not applicable.

**MAL code number according to Executive Order no. 301 from 13 May 1993 on the determination of code numbers (The Danish Working Environment Service)**

MAL code number 5-5

##### Additional information

##### Substance/product listed in the following inventories

Substance/product listed in the following inventories TSCA • EINECS/ELINCS • REACH

#### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information

#### 16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling

#### 16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

ASTM = American Society of Testing and Materials (US)

CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)

DNEL = Derived No-Effect Level

DT50 = Time for 50% loss; half-life

EbC50 = Median effective concentration (biomass, e.g. of algae)

EC50 = Median effective concentration

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)

ErC50 = Median effective concentration (growth rate, e.g. of algae)

EWC = European Waste Catalogue

IATA = International Air Transport Association

IC50 = Concentration that produces 50% inhibition

IMDG = International Maritime Dangerous Goods Code

IMO = International Maritime Organization

LC50 = Concentration required to kill 50% of test organisms

LD50 = Dose required to kill 50% of test organisms

LEL = Lower Explosive Limit/Lower Explosion Limit

LOAEL = Lowest observed adverse effect level

MRL = Maximum Residue Limit

NOAEL = No Observed Adverse Effect Level

NOEC = No observed effect concentration

NOEL = No Observable Effect Level

OEL = Occupational Exposure Limits

PBT = Persistent, Bioaccumulative or Toxic

PNEC = Previsible Non Effect Concentration

STEL = Short-Term Exposure Limit

TWA = Time-Weighted Average

vPvB = Very Persistent and Very Bioaccumulative

#### 16.3 Key literature references and sources for data

None

Trade name : Wencon Hi-Temp Green - Component A  
Revision date : 25.03.2023  
Print date : 25-03-2023

Version (Revision) : 8.0.0 (7.0.0)

---

**16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

No information available.

**16.5 Relevant H- and EUH-phrases (Number and full text)**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**16.6 Training advice**

The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

**16.7 Additional information**

This safety data sheet contains more than one ES in an integrated form. Contents of the exposure scenarios have been included into sections 1.2, 8, 9, 12, 15 and 16 of this safety data sheet.

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---