

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Wencon Ceramic Coating Light Green - Component A (285000100A)
PR-number (Danish): 2347834

1.2 Relevant identified uses of the substance or mixture and uses advised against

Solventfree two component filler compound based on epoxy

Relevant identified uses

In compliance with the conditions described in the annex to this safety data sheet. See section 16 for a comprehensive list of uses, for which an exposure scenario is provided as an annex.

Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC 19 - Manual activities involving hand contact

PROC 21 - Low energy manipulation of substances bound in materials and/or articles

PROC 24 - High (mechanical) energy work-up of substances bound in/on materials and/or articles

Environmental release categories [ERC]

ERC 8c - Widespread use leading to inclusion into/onto article (indoor)

ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

ERC 10a - Widespread use of articles with low release (outdoor)

ERC 11a - Widespread use of articles with low release (indoor)

Article categories [AC]

AC 7 - Metal articles

Uses advised against

Do not use for private purposes (household).

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer) : Wencon ApS

Street : Jyllandsvej 15

Postal code/City : DK-5400 BOGENSE

Telephone : +45 6481 1010

Information contact : wencon@wencon.com

1.4 Emergency telephone number

+44 870 600 62 66 (UK National Poisons Emergency Number)

European emergency number: 112. Danmark: (Giftlinjen +45 82 12 12 12), only for the purpose of informing medical personnel in cases of acute intoxications.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Irrit. 2 ; H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

Repr. 1B ; H360F - Reproductive toxicity : Category 1B ; May damage fertility.

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long lasting effects.

Additional information

This preparation is classified as UN packing group (GHS subcategory) non-corrosive in accordance with OECD 435

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

(In vitro membrane barrier test method for skin corrosion) and Part III, Section 37 of the UN Testing Manual (Classification procedures, test methods and criteria relating to substances of class 8).

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Health hazard (GHS08) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER ; CAS No. : 28064-14-4
EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5
BIS-[4-(2,3-EPOXIPROPONI)PHENYL]PROPANE ; CAS No. : 1675-54-3
REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9
BIS-[4-(2,3-EPOXIPROPONI)PHENYL]PROPANE ; CAS No. : 1675-54-3
BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW ≤ 700 ; CAS No. : 9003-36-5
PHENOL, METHYL STYRENATED ; CAS No. : 68512-30-1
2,3-EPOXYPROPYL NEODECANOATE ; CAS No. : 26761-45-5

Hazard statements

H360F May damage fertility.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P405 Store locked up.

Special rules for supplemental label elements for certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray, or mist.

Remark

This preparation is classified as UN packing group (GHS subcategory) non-corrosive in accordance with OECD 435 (In vitro membrane barrier test method for skin corrosion) and Part III, Section 37 of the UN Testing Manual (Classification procedures, test methods and criteria relating to substances of class 8).

2.3 Other hazards

Adverse human health effects and symptoms

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meet the criteria.

Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meet the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

3.2 Mixtures

Hazardous ingredients

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER ; EC No. : 608-164-0; CAS No. : 28064-14-4

Weight fraction : $\geq 20 - < 25 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

EPOXY PHENOL NOVOLAK RESIN ; REACH No. : 01-2119454392-40 ; EC No. : 701-263-0; CAS No. : 9003-36-5

Weight fraction : $\geq 15 - < 20 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

BIS-[4-(2,3-EPOXI-PROPOXI)PHENYL]PROPANE ; REACH No. : 01-2119456619-26 ; EC No. : 216-823-5; CAS No. : 1675-54-3

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319

Specific Conc. Limits : Eye Irrit. 2 ; H319: C $\geq 5 \%$ • Skin Irrit. 2 ; H315: C $\geq 5 \%$

TITANIUM DIOXIDE ; EC No. : 236-675-5; CAS No. : 13463-67-7

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Carc. 2 ; H351 (Inhalation)

REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; REACH No. : 01-2119463471-41 ; EC No. : 618-939-5; CAS No. : 933999-84-9

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Repr. 1B ; H360F Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319

QUARTZ (SiO₂) ; REACH No. : Annex V ; EC No. : 238-878-4; CAS No. : 14808-60-7

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : None

BIS-[4-(2,3-EPOXI-PROPOXI)PHENYL]PROPANE ; REACH No. : 01-2119456619-26 ; EC No. : 216-823-5; CAS No. : 1675-54-3

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

Specific Conc. Limits : Eye Irrit. 2 ; H319: C $\geq 5 \%$ • Skin Irrit. 2 ; H315: C $\geq 5 \%$

BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW ≤ 700 ; REACH No. : 01-211-454392-40 ; EC No. : 500-006-8; CAS No. : 9003-36-5

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

PHENOL, METHYL STYRENATED ; REACH No. : 01-2119555274-38 ; EC No. : 270-966-8; CAS No. : 68512-30-1

Weight fraction : $< 0,5 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Chronic 3 ; H412

2,3-EPOXYPROPYL NEODECANOATE ; REACH No. : 01-211943157-33 ; EC No. : 247-979-2; CAS No. : 26761-45-5

Weight fraction : $< 0,5 \%$

Classification 1272/2008 [CLP] : Muta. 2 ; H341 Skin Sens. 1A ; H317 Aquatic Chronic 2 ; H411

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label.

In case of skin contact

In case of skin reactions, consult a physician. Immediately remove any contaminated clothing, shoes or stockings. After contact with skin, wash immediately with plenty of water and soap. Do not use force or solvents to remove product incrustations from affected skin areas. Do not let product dry on skin.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Following ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam

Unsuitable extinguishing media

Water spray jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Use suitable breathing apparatus.

Hazardous combustion products

Carbon monoxide

5.3 Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Do not breathe gas/fumes/vapour/spray. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Use personal protection equipment. See protective measures under point 7 and 8.

For emergency responders

Do not breathe gas/fumes/vapour/spray. Use personal protection equipment. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains,

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

inform the responsible authorities. Ensure waste is collected and contained.

6.3 Methods and material for containment and cleaning up

For containment

Ensure waste is collected and contained.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation. Clean with detergents. Avoid solvent cleaners. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

None

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Protective measures

Persons with a history of skin sensitisation problems should not be employed in any process in which this product is used. It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). Never use pressure to empty container. Use only in well-ventilated areas.

Measures to prevent fire

Keep away from sources of ignition - No smoking.

Environmental precautions

Do not allow to enter into surface water or drains.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Only use containers specifically approved for the substance/product. Keep/Store only in original container. Keep container tightly closed.

Hints on joint storage

Keep away from:

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place. Store in a place accessible by authorized persons only. Handle and open container with care.

7.3 Specific end use(s)

Observe instructions for use. The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

()

DNEL-/PNEC-values

DNEL/DMEL

EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5

Limit value type : DNEL worker (local)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 8,3 µg/cm²
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 29,39 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 104,15 mg/m³ bw/day
BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW ≤ 700 ; CAS No. : 9003-36-5
Limit value type : DNEL worker (local)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 8,3 µg/cm²
Limit value type : DNEL worker (systemic)
Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 29,39 mg/m³
Limit value type : DNEL worker (systemic)
Exposure route : Dermal
Exposure frequency : Long-term
Limit value : 104,15 mg/m³ bw/day

8.2 Exposure controls

Personal protection equipment



Eye/face protection

Suitable eye protection

Eye glasses with side protection

Skin protection

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Wear cotton undermitten if possible.

Suitable gloves type : Disposable gloves.

Suitable material : NBR (Nitrile rubber)

Required properties : liquid-tight.

Breakthrough time : > 60 minutes

Thickness of the glove material : > 0.5 mm

Recommended glove articles : EN 374

Additional hand protection measures : Do not wear gloves near rotary machines and tools. Check leak tightness/impermeability prior to use. Wear cotton undermitten if possible. Use gloves only once. Take recovery periods for skin regeneration.

Remark : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Observe the wear time limits as specified by the manufacturer. Breakthrough times and swelling properties of the material must be taken into consideration. In the case of wanting to use the gloves again, clean them before taking off and air them well. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Barrier creams are not substitutes for body protection.

Body protection

Remark : Body protection: not required.

Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values
If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Suitable respiratory protection apparatus

Combination filtering device Filtering device (EN 147) Full-/half-/quarter-face masks (EN 136/140) Filtering Half-face mask (EN 149) Particle filter device (EN 143).

Filtering device (full mask or mouthpiece) with filter: A P

Additional measures for respiratory protection

Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.) Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo. Full-face mask or mouthpiece with particulate filter: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 15 times the exposure limit. P3 filter: up to a max. of

Remark

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General information

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Immediately remove any contaminated clothing, shoes or stockings.

Other protection measures

Further information: see technical data sheet.

Further information: see technical data sheet.

Further information: see technical data sheet.

Technical measures and the application of suitable work processes have priority over personal protection equipment. See section 7. No additional measures necessary.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Paste

Appearance

Colour : light green

Odour

characteristic

Safety characteristics

Flash point :	>	100	°C	DIN 53213-1
Evaporation rate :	<	1		
Vapour pressure :	(50 °C)	<	1000	hPa
Density :	(20 °C)	approx.	1,55	g/cm ³ DIN 53217
Melting point/freezing point :	not applicable			
Initial boiling point and boiling range :	No data available			
Decomposition temperature :	No data available			
Auto-ignition temperature :	No data available			
Flammable gases :	Not applicable.			
Flammable solids :	Not applicable.			
Oxidising properties.	No data available.			
Lower explosion limit :	No data available			

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

Upper explosion limit : No data available
Explosive properties : No data available.
Relative vapour density : No data available
Water solubility : practically insoluble
Partition coefficient n-octanol/water : No data available
pH : No data available
Flow time : not determined
Viscosity : not applicable
Kinematic viscosity : No data available
Odour threshold : No data available
- BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700; CAS No. : 9003-36-5
Initial boiling point and boiling range : (1000 hPa) 90 °C

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Ignition hazard.

10.5 Incompatible materials

Exothermic reaction with: Amines.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute toxicity

Acute oral toxicity

Parameter :	LD50 (EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg
Parameter :	LC50 (REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9)
Exposure route :	Oral
Species :	Rat
Effective dose :	2190 mg/kg
Parameter :	LD50 (BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5)
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg
Parameter :	LD50 (2,3-EPOXYPROPYL NEODECANOATE ; CAS No. : 26761-45-5)
Exposure route :	Oral

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

Species : Rat
Effective dose : > 2000 mg/kg

Acute dermal toxicity

Parameter : LD50 (EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5)

Exposure route : Dermal

Species : Rat

Effective dose : > 2000 mg/kg

Parameter : LC50 (REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9)

Exposure route : Dermal

Species : Rat

Effective dose : > 2000 mg/kg

Parameter : LD50 (BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5)

Exposure route : Dermal

Species : Rat

Effective dose : > 2000 mg/kg

Parameter : LD50 (2,3-EPOXYPROPYL NEODECANOATE ; CAS No. : 26761-45-5)

Exposure route : Dermal

Species : Rat

Effective dose : > 2000 mg/kg

Respiratory or skin sensitisation

EUH205 - Contains epoxy constituents. May produce an allergic reaction. Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. Risk of serious damage to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

Skin sensitisation

Parameter : Skin sensitisation (EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5)

Species : Guinea pig

Effective dose : 50 %

Result : Sensitising.

Method : OECD 406

Parameter : Skin sensitisation (BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5)

Species : Guinea pig

Effective dose : 50 %

Result : Sensitising.

Method : OECD 406

Practical experience/human evidence

Causes skin irritation. Causes serious eye irritation.

11.2 Information on other hazards

No information available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : Acute (short-term) fish toxicity (EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5)

Species : Acute (short-term) fish toxicity

Effective dose : 2,54 mg/l

Exposure time : 96 h

Parameter : LC50 (EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5)

Species : Fish

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

Effective dose : 2,54 mg/l
Exposure time : 96 h
Parameter : LC50 (REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9)
Species : Leuciscus idus (golden orfe)
Effective dose : 30 mg/l
Exposure time : 96 h
Parameter : EC50 (REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9)
Species : Algae
Effective dose : 23,1 mg/l
Exposure time : 48 h
Parameter : EC50 (REACTION PRODUCTS OF HEXANE-1,6-DIOL WITH 2-(CHLOROMETHYL)OXIRANE ; CAS No. : 933999-84-9)
Species : Daphnia magna (Big water flea)
Effective dose : 47 mg/l
Exposure time : 48 h
Parameter : Acute (short-term) fish toxicity (BISPENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5)
Species : Acute (short-term) fish toxicity
Effective dose : 2,54 mg/l
Exposure time : 96 h

Acute (short-term) toxicity to aquatic invertebrates

Parameter : EC50 (EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5)
Species : Daphnia magna (Big water flea)
Effective dose : 2,55 mg/l
Exposure time : 48 h
Parameter : EC50 (EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5)
Species : Algae
Effective dose : 1,8 mg/l
Exposure time : 72 h

12.2 Persistence and degradability

Biodegradation

Parameter : Biodegradation (EPOXY PHENOL NOVOLAK RESIN ; CAS No. : 9003-36-5)
Inoculum : Biodegradation
Degradation rate : 16 %
Test duration : 28
Evaluation : Not readily biodegradable (according to OECD criteria)
Method : OECD 301B
Parameter : Biodegradation (BISPENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW <= 700 ; CAS No. : 9003-36-5)
Inoculum : Biodegradation
Degradation rate : 16 %
Test duration : 28
Evaluation : Not readily biodegradable (according to OECD criteria)
Method : OECD 301B

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

No information available.

12.8 Additional ecotoxicological information

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3). Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No information available.

SECTION 14: Transport information

14.1 UN number or ID number

UN 3082

14.2 UN proper shipping name

Land transport (ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER · EPOXY PHENOL NOVOLAK RESIN)

Sea transport (IMDG)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER · EPOXY PHENOL NOVOLAK RESIN · BIS-[4-(2,3-EPOXI-PROPOXI)PHENYL]PROPANE · BISPHENOL F-(EPICHLORHYDRIN); EPOXY RESIN MW ≤ 700)

Air transport (ICAO-TI / IATA-DGR)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER · EPOXY PHENOL NOVOLAK RESIN)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 9
Classification code : M6
Hazard identification number (Kemler No.) : 90
Tunnel restriction code : -
Special Provisions : LQ 5 l · E 1 · ADR : - (SP 375 ≤ 5 l/kg)
Hazard label(s) : 9 / N

Sea transport (IMDG)

Class(es) : 9
EmS-No. : F-A / S-F
Special Provisions : LQ 5 l · E 1 · IMDG : - (SP 2.10.2.7 ≤ 5 l/kg)
Hazard label(s) : 9 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 9
Special Provisions : E 1 · IATA : - (SP A197 ≤ 5 l/kg)
Hazard label(s) : 9 / N

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : Yes
Sea transport (IMDG) : Yes (P)
Air transport (ICAO-TI / IATA-DGR) : Yes

14.6 Special precautions for user

None

14.8 Additional information

This preparation is classified as UN packing group (GHS subcategory) non-corrosive in accordance with OECD 435

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

(In vitro membrane barrier test method for skin corrosion) and Part III, Section 37 of the UN Testing Manual (Classification procedures, test methods and criteria relating to substances of class 8).

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 75

National regulations

Directive 2004/42/EC is not applicable.

Störfallverordnung (12. BlmschV)

Hazard categories

This product is not assigned to a hazard category.

Other regulations, restrictions and prohibition regulations

Denmark

MAL Code

MAL Code : 5-5

Additional information

Substance/product listed in the following inventories

Substance/product listed in the following inventories TSCA • EINECS/ELINCS • REACH

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 14. UN proper shipping name - Land transport (ADR/RID) · 14. UN proper shipping name - Sea transport (IMDG) · 14. UN proper shipping name - Air transport (ICAO-TI / IATA-DGR) · 15. Restrictions on use

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM = American Society of Testing and Materials (US)
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)
DNEL = Derived No-Effect Level
DT50 = Time for 50% loss; half-life
EbC50 = Median effective concentration (biomass, e.g. of algae)
EC50 = Median effective concentration
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)
ErC50 = Median effective concentration (growth rate, e.g. of algae)
EWC = European Waste Catalogue
IATA = International Air Transport Association
IC50 = Concentration that produces 50% inhibition
IMDG = International Maritime Dangerous Goods Code
IMO = International Maritime Organization
LC50 = Concentration required to kill 50% of test organisms
LD50 = Dose required to kill 50% of test organisms
LEL = Lower Explosive Limit/Lower Explosion Limit
LOAEL = Lowest observed adverse effect level
MRL = Maximum Residue Limit

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component A
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 8.0.0 (7.0.0)

NOAEL = No Observed Adverse Effect Level
NOEC = No observed effect concentration
NOEL = No Observable Effect Level
OEL = Occupational Exposure Limits
PBT = Persistent, Bioaccumulative or Toxic
PNEC = Previsible Non Effect Concentration
STEL = Short-Term Exposure Limit
TWA = Time-Weighted Average
vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer if inhaled.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6 Training advice

The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

16.7 Additional information

This safety data sheet contains more than one ES in an integrated form. Contents of the exposure scenarios have been included into sections 1.2, 8, 9, 12, 15 and 16 of this safety data sheet.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Wencon Ceramic Coating Light Green - Component B (285000100B)
PR-number (Danish): 2347850

1.2 Relevant identified uses of the substance or mixture and uses advised against

Solventfree two component filler compound based on epoxy

Relevant identified uses

In compliance with the conditions described in the annex to this safety data sheet. See section 16 for a comprehensive list of uses, for which an exposure scenarion is provided as an annex.

Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC 19 - Manual activities involving hand contact

PROC 21 - Low energy manipulation of substances bound in materials and/or articles

PROC 24 - High (mechanical) energy work-up of substances bound in/on materials and/or articles

Environmental release categories [ERC]

ERC 8c - Widespread use leading to inclusion into/onto article (indoor)

ERC 8f - Widespread use leading to inclusion into/onto article (outdoor)

ERC 10a - Widespread use of articles with low release (outdoor)

ERC 11a - Widespread use of articles with low release (indoor)

Article categories [AC]

AC 7 - Metal articles

Uses advised against

Do not use for private purposes (household).

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer) : Wencon ApS

Street : Jyllandsvej 15

Postal code/City : DK-5400 BOGENSE

Telephone : +45 6481 1010

Information contact : wencon@wencon.com

1.4 Emergency telephone number

+44 870 600 62 66 (UK National Poisons Emergency Number)

European emergency number: 112. Danmark: (Giftlinjen +45 82 12 12 12), only for the purpose of informing medical personnel in cases of acute intoxications.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 ; H302 - Acute toxicity (oral) : Category 4 ; Harmful if swallowed.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

Repr. 1B ; H360F - Reproductive toxicity : Category 1B ; May damage fertility.

ED HH 1 ; EUH380 - Endocrine disruptor for human health : Category 1 ; May cause endocrine disruption in humans.

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Chronic 2 ; Toxic to aquatic life with long

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

lasting effects.

ED ENV 1 ; EUH430 - Endocrine disruptor for the environment : Category 1 ; May cause endocrine disruption in the environment.

Additional information

This preparation is classified as UN packing group (GHS subcategory) non-corrosive in accordance with OECD 435 (In vitro membrane barrier test method for skin corrosion) and Part III, Section 37 of the UN Testing Manual (Classification procedures, test methods and criteria relating to substances of class 8).

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Health hazard (GHS08) · Corrosion (GHS05) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Danger

Hazard components for labelling

BENZYL ALCOHOL ; CAS No. : 100-51-6
M-PHENYLENEBIS(METHYLAMINE) ; CAS No. : 1477-55-0
BADGE-IPDA ADDUCT ; CAS No. : 38294-64-3
4,4'-ISOPROPYLIDENEDIPHENOL ; CAS No. : 80-05-7
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS No. : 2855-13-2

Hazard statements

H360F May damage fertility.
H318 Causes serious eye damage.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
EUH380 May cause endocrine disruption in humans.
H411 Toxic to aquatic life with long lasting effects.
EUH430 May cause endocrine disruption in the environment.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P263 Avoid contact during pregnancy and while nursing.
P264 Wash hands thoroughly after handling.
P310 Immediately call a POISON CENTER.
P321 Specific treatment (see supplemental first aid instructions on this label).
P405 Store locked up.

Special rules for supplemental label elements for certain mixtures

O220 Restricted to professional users.

Remark

This preparation is classified as UN packing group (GHS subcategory) non-corrosive in accordance with OECD 435 (In vitro membrane barrier test method for skin corrosion) and Part III, Section 37 of the UN Testing Manual (Classification procedures, test methods and criteria relating to substances of class 8).

2.3 Other hazards

Adverse human health effects and symptoms

The mixture contains $\geq 0.1\%$ of substances that have endocrine disrupting properties. See SECTION 3 of this safety data sheet.

- 4,4'-ISOPROPYLIDENEDIPHENOL ; CAS No. : 80-05-7 ; EC No. : 201-245-8 ; Index No. : 604-030-00-0

Adverse environmental effects

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

The mixture contains $\geq 0.1\%$ of substances that have endocrine disrupting properties. See SECTION 3 of this safety data sheet.

- 4,4'-ISOPROPYLIDENEDIPHENOL ; CAS No. : 80-05-7 ; EC No. : 201-245-8 ; Index No. : 604-030-00-0

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

BENZYL ALCOHOL ; REACH No. : 01-2119492630-38 ; EC No. : 202-859-9 ; CAS No. : 100-51-6

Weight fraction : $\geq 15 - < 20 \%$

Classification 1272/2008 [CLP] : Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Skin Sens. 1B ; H317 Eye Irrit. 2 ; H319

Specific Conc. Limits : (ATE - oral : 1200 mg/kg)

M-PHENYLENEBIS(METHYLAMINE) ; REACH No. : 01-2119480150-50 ; EC No. : 216-032-5 ; CAS No. : 1477-55-0

Weight fraction : $\geq 10 - < 15 \%$

Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Acute Tox. 4 ; H332 Skin Sens. 1B ; H317 Aquatic Chronic 3 ; H412 EUH071

BADGE-IPDA ADDUCT ; REACH No. : 01-2119965165-33 ; EC No. : 500-101-4 ; CAS No. : 38294-64-3

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Skin Sens. 1 ; H317 Aquatic Chronic 3 ; H412

4,4'-ISOPROPYLIDENEDIPHENOL ; REACH No. : 01-211945856-23 ; EC No. : 201-245-8 ; CAS No. : 80-05-7

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Repr. 1B ; H360F Eye Dam. 1 ; H318 Skin Sens. 1 ; H317 STOT SE 3 ; H335 ED HH 1 ; EUH380 Aquatic Acute 1 ; H400 Aquatic Chronic 1 ; H410 ED ENV 1 ; EUH430

Specific Conc. Limits : (M Chronic=10) • (M Acute=1)

POLYOXYPROPYLENE DIAMINE ; REACH No. : 01-2119557899-12 ; EC No. : 618-561-0 ; CAS No. : 9046-10-0

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Aquatic Chronic 3 ; H412

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; REACH No. : 01-2119514687-32 ; EC No. : 220-666-8 ; CAS No. : 2855-13-2

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Acute Tox. 4 ; H302 Skin Sens. 1A ; H317

Specific Conc. Limits : Skin Sens. 1A ; H317: C $\geq 0,001 \%$ • (ATE - oral : 1030 mg/kg)

3-CYCLOHEXYLAMINO PROPYLAMINE ; REACH No. : 01-2120817177-54 ; EC No. : 222-001-7 ; CAS No. : 3312-60-5

Weight fraction : $\geq 1 - < 5 \%$

Classification 1272/2008 [CLP] : Acute Tox. 3 ; H301 Acute Tox. 3 ; H311 Skin Corr. 1B ; H314 Eye Dam. 1 ; H318 Aquatic Chronic 3 ; H412

Contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH

4,4'-ISOPROPYLIDENEDIPHENOL ; REACH No. : 01-211945856-23 ; EC No. : 201-245-8 ; CAS No. : 80-05-7

Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

respiration. Consult a doctor immediately in the case of inhaling spray mist and show him packing or label.

In case of skin contact

In case of skin reactions, consult a physician. Immediately remove any contaminated clothing, shoes or stockings. After contact with skin, wash immediately with plenty of water and soap. Do not use force or solvents to remove product incrustations from affected skin areas. Do not let product dry on skin.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Following ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam

Unsuitable extinguishing media

Water spray jet

5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Use suitable breathing apparatus.

Hazardous combustion products

Carbon monoxide

5.3 Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Do not breathe gas/fumes/vapour/spray. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Use personal protection equipment. See protective measures under point 7 and 8.

For emergency responders

Do not breathe gas/fumes/vapour/spray. Use personal protection equipment. See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Ensure waste is collected and contained.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

6.3 Methods and material for containment and cleaning up

For containment

Ensure waste is collected and contained.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation. Clean with detergents. Avoid solvent cleaners. Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

None

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Protective measures

Persons with a history of skin sensitisation problems should not be employed in any process in which this product is used. It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). Never use pressure to empty container. Use only in well-ventilated areas.

Measures to prevent fire

Keep away from sources of ignition - No smoking.

Environmental precautions

Do not allow to enter into surface water or drains.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Only use containers specifically approved for the substance/product. Keep/Store only in original container. Keep container tightly closed.

Hints on joint storage

Keep away from:

Further information on storage conditions

Keep only in the original container in a cool, well-ventilated place. Store in a place accessible by authorized persons only. Handle and open container with care.

7.3 Specific end use(s)

Observe instructions for use. The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

4,4'-ISOPROPYLIDENEDIPHENOL ; CAS No. : 80-05-7

Limit value type (country of origin) : TWA (EC)

Parameter : E: inhalable fraction

Limit value : 2 mg/m³

Version : 09-03-2022

8.2 Exposure controls

Personal protection equipment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)



Eye/face protection

Suitable eye protection

Eye glasses with side protection

Skin protection

Hand protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Wear cotton undermitten if possible.

Suitable gloves type : Disposable gloves.

Suitable material : NBR (Nitrile rubber)

Required properties : liquid-tight.

Breakthrough time : > 60 minutes

Thickness of the glove material : > 0.5 mm

Recommended glove articles : EN 374

Additional hand protection measures : Do not wear gloves near rotary machines and tools. Check leak tightness/impermeability prior to use. Wear cotton undermitten if possible. Use gloves only once. Take recovery periods for skin regeneration.

Remark : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Observe the wear time limits as specified by the manufacturer. Breakthrough times and swelling properties of the material must be taken into consideration. In the case of wanting to use the gloves again, clean them before taking off and air them well. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Barrier creams are not substitutes for body protection.

Body protection

Remark : Body protection: not required.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Suitable respiratory protection apparatus

Combination filtering device Filtering device (EN 147) Full-/half-/quarter-face masks (EN 136/140) Filtering Half-face mask (EN 149) Particle filter device (EN 143).

Filtering device (full mask or mouthpiece) with filter: A P

Additional measures for respiratory protection

Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.) Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo. Full-face mask or mouthpiece with particulate filter: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 15 times the exposure limit. P3 filter: up to a max. of

Remark

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

General information

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Immediately remove any contaminated clothing, shoes or stockings.

Other protection measures

Further information: see technical data sheet.

Further information: see technical data sheet.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

Further information: see technical data sheet.

Technical measures and the application of suitable work processes have priority over personal protection equipment. See section 7. No additional measures necessary.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Paste

Appearance

Colour : grey

Odour

Amines

Safety characteristics

Flash point :	>	100	°C	DIN 53213-1
Evaporation rate :	<	1		
Vapour pressure :	(50 °C)	<	1000	hPa
Density :	(20 °C)	approx.	1,3	g/cm³
pH :			6 - 8	DIN 53217
Melting point/freezing point :	not applicable			
Initial boiling point and boiling range				
:	No data available			
Decomposition temperature :	No data available			
Auto-ignition temperature :	No data available			
Flammable gases :	Not applicable.			
Flammable solids :	Not applicable.			
Oxidising properties.	No data available.			
Lower explosion limit :	No data available			
Upper explosion limit :	No data available			
Explosive properties :	No data available.			
Relative vapour density :	No data available			
Water solubility :	practically insoluble			
Partition coefficient n-octanol/water				
:	No data available			
Flow time :	not determined			
Viscosity :	not applicable			
Kinematic viscosity :	No data available			
Odour threshold :	No data available			
- BENZYL ALCOHOL; CAS No. : 100-51-6				
Initial boiling point and boiling				
range :	(1000 hPa)	106	°C	

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

10.4 Conditions to avoid

Ignition hazard.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute toxicity

Acute oral toxicity

Parameter :	LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Oral
Species :	Rat
Effective dose :	1230 mg/kg
Parameter :	LD50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Oral
Species :	Mouse
Effective dose :	1600 mg/kg
Parameter :	LD50 (M-PHENYLENEBIS(METHYLAMINE) ; CAS No. : 1477-55-0)
Exposure route :	Oral
Species :	Rat
Effective dose :	1200 mg/kg
Parameter :	LD50 (POLYOXYPROPYLENE DIAMINE ; CAS No. : 9046-10-0)
Exposure route :	Oral
Species :	Rat
Effective dose :	580 mg/kg

Acute dermal toxicity

Parameter :	LD50 (M-PHENYLENEBIS(METHYLAMINE) ; CAS No. : 1477-55-0)
Exposure route :	Dermal
Species :	Rat
Effective dose :	2000 mg/kg
Parameter :	LD50 (POLYOXYPROPYLENE DIAMINE ; CAS No. : 9046-10-0)
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	670 mg/kg

Acute inhalation toxicity

Parameter :	LC50 (BENZYL ALCOHOL ; CAS No. : 100-51-6)
Exposure route :	Inhalation
Species :	Rat
Effective dose :	1000 ppm
Exposure time :	8 h

Respiratory or skin sensitisation

Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

Skin sensitisation

Practical experience/human evidence

Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc. Causes burns. Causes serious eye damage.

11.2 Information on other hazards

No information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

No information available.

12.7 Other adverse effects

No information available.

12.8 Additional ecotoxicological information

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3). Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No information available.

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.8 Additional information

This preparation is classified as UN packing group (GHS subcategory) non-corrosive in accordance with OECD 435 (In vitro membrane barrier test method for skin corrosion) and Part III, Section 37 of the UN Testing Manual (Classification procedures, test methods and criteria relating to substances of class 8).

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

Authorisations and/or restrictions on use

Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no. : 3, 30, 66, 75

National regulations

Directive 2004/42/EC is not applicable.

Störfallverordnung (12. BlmschV)

Hazard categories

This product is not assigned to a hazard category.

Other regulations, restrictions and prohibition regulations

Denmark

MAL Code

MAL Code : 3-5

Additional information

Substance/product listed in the following inventories

Substance/product listed in the following inventories TSCA • EINECS/ELINCS • REACH

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Classification of the substance or mixture · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 08. Occupational exposure limit values · 15. Restrictions on use

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM = American Society of Testing and Materials (US)
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)
DNEL = Derived No-Effect Level
DT50 = Time for 50% loss; half-life
EbC50 = Median effective concentration (biomass, e.g. of algae)
EC50 = Median effective concentration
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)
ErC50 = Median effective concentration (growth rate, e.g. of algae)
EWC = European Waste Catalogue
IATA = International Air Transport Association
IC50 = Concentration that produces 50% inhibition
IMDG = International Maritime Dangerous Goods Code
IMO = International Maritime Organization
LC50 = Concentration required to kill 50% of test organisms
LD50 = Dose required to kill 50% of test organisms
LEL = Lower Explosive Limit/Lower Explosion Limit
LOAEL = Lowest observed adverse effect level
MRL = Maximum Residue Limit
NOAEL = No Observed Adverse Effect Level
NOEC = No observed effect concentration
NOEL = No Observable Effect Level
OEL = Occupational Exposure Limits
PBT = Persistent, Bioaccumulative or Toxic
PNEC = Predictable Non Effect Concentration
STEL = Short-Term Exposure Limit
TWA = Time-Weighted Average
vPvB = Very Persistent and Very Bioaccumulative

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Wencon Ceramic Coating Light Green - Component B
Revision date : 28.03.2025
Print date : 29-04-2025

Version (Revision) : 11.0.0 (10.0.0)

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

EUH380	May cause endocrine disruption in humans.
EUH430	May cause endocrine disruption in the environment.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

16.6 Training advice

The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

16.7 Additional information

This safety data sheet contains more than one ES in an integrated form. Contents of the exposure scenarios have been included into sections 1.2, 8, 9, 12, 15 and 16 of this safety data sheet.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.