

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

WENCON PUTTY (99900100)  
UFI: D300-W0XG-F00P-G5T9

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

In compliance with the conditions described in the annex to this safety data sheet. See section 16 for a comprehensive list of uses, for which an exposure scenario is provided as an annex.

#### Uses advised against

Do not use for private purposes (household).

#### Remark

The product is intended for professional use.

### 1.3 Details of the supplier of the safety data sheet

**Supplier (manufacturer) :** Wencon ApS

**Street :** Jyllandsvej 15

**Postal code/City :** DK-5400 BOGENSE

**Telephone :** +45 6481 1010

**Responsible for the safety data sheet (e-mail):** wencon@wencon.com

### 1.4 Emergency telephone number

+44 870 600 62 66 (UK National Poisons Emergency Number)

NHS (England or Wales): Dial 111 or 0845 4647. NHS 24 (Scotland): Dial 111

National Poisons Information Centre (Ireland): +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week)

Healthcare Professionals: +353 (1) 809 2566 (24-hour service)

European emergency number: 112.

Denmark: (Giftlinjen +45 82 12 12 12), only for the purpose of informing medical personnel in cases of acute intoxications.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens. 1;H317 Aquatic Chronic 3;H412

### 2.2 Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Exclamation mark (GHS07)

**Signal word**

Warning

**Hazard components for labelling**

2,2-BIS-(4-(2,3-EPOXYPROPOXY) PHENYL) PROPANE, POLYMER

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700)

**Hazard statements**

H315 Causes skin irritation.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P261 Avoid breathing vapours/spray.  
P264 Wash hands thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection.  
P337+P313 If eye irritation persists: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.

Special rules for supplemental label elements for certain mixtures: Not relevant

## 2.3 Other hazards

### Adverse human health effects and symptoms

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### Adverse environmental effects

This product does not contain a substance that has endocrine disrupting properties in accordance with the criteria set out in Regulation 2023/707.

The substances in the mixture do not meet the PBT/vPvB criteria according to criteria in Regulation 2023/707.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

2,2-BIS-(4-(2,3-EPOXYPROPOXY) PHENYL) PROPANE, POLYMER; CAS No.: 25085-99-8

Weight fraction :  $\geq 10 - < 25 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER; EC No. : 608-164-0; CAS No. : 28064-14-4

Weight fraction :  $\geq 2.5 - < 10 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319  
Aquatic Chronic 2;H411

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL; REACH No. : 01-211950597-27; EC No. : 202-013-9; CAS No. : 90-72-2;  
Index No.: 603-069-00-0

Weight fraction :  $\geq 1 - < 2.5 \%$

Classification 1272/2008 [CLP] : Acute Tox. 4;H302 Skin Irrit. 2;H315 Eye Irrit. 2;H319

ATE (oral) = 1673 mg/kg

CARBON BLACK ; REACH No. : 01-2119384822-32; EC No. : 215-609-9; CAS No. : 1333-86-4

Weight fraction :  $\geq 1 - < 2.5 \%$

Classification 1272/2008 [CLP] : None

QUARTZ (SIO<sub>2</sub>); REACH No. : None; EC No.: 238-878-4; CAS No.: 14808-60-7

Weight fraction :  $\geq 1 - < 2.5 \%$

Classification 1272/2008 [CLP] : None

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT  $\leq 700$ );  
REACH No.: 01-2119456619-26; EC No.: 500-033-5; CAS No.: 25068-38-6; Index No.: 603-074-00-8

Weight fraction :  $< 0.5 \%$

Classification 1272/2008 [CLP] : Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Aquatic Chronic 2;H411

Specific Conc. Limits : Eye Irrit. 2;H319: C  $\geq 5\%$ ; Skin Irrit. 2;H315: C  $\geq 5\%$

#### Additional information

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately. If unconscious but breathing normally, place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### In case of skin contact

In case of skin reactions, consult a physician. Immediately remove any contaminated clothing, shoes or stockings. After contact with skin, wash immediately with plenty of water and soap. Do not use force or solvents to remove product incrustations from affected skin areas. Do not let product dry on skin.

#### After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### Following ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam

#### Unsuitable extinguishing media

Water spray jet

### 5.2 Special hazards arising from the substance or mixture

Burning produces heavy smoke. Use suitable breathing apparatus.

#### Hazardous combustion products

Oxides of carbon and nitrogen.

### 5.3 Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

#### **For non-emergency personnel**

Do not breathe gas/fumes/vapour/spray. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Use personal protection equipment. See protective measures under point 7 and 8.

#### **For emergency responders**

Do not breathe gas/fumes/vapour/spray. Use personal protection equipment. See protective measures under point 7 and 8.

#### **6.2 Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Ensure waste is collected and contained.

#### **6.3 Methods and material for containment and cleaning up**

##### **For containment**

Ensure waste is collected and contained.

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation. Clean with detergents. Avoid solvent cleaners. Treat the recovered material as prescribed in the section on waste disposal.

#### **6.4 Reference to other sections**

None

### **SECTION 7: Handling and storage**



#### **7.1 Precautions for safe handling**

##### **Protective measures**

It is recommended to design all work processes always so that the following is excluded: Inhalation of vapours or spray/mists  
Skin contact Eye contact Do not breathe gas/fumes/vapour/spray. When using do not eat, drink, smoke, sniff. Wear personal protection equipment (refer to section 8). Never use pressure to empty container. Use only in well-ventilated areas.

##### **Measures to prevent fire**

Keep away from sources of ignition - No smoking.

##### **Environmental precautions**

Do not allow to enter into surface water or drains.

#### **7.2 Conditions for safe storage, including any incompatibilities**

##### **Requirements for storage rooms and vessels**

Only use containers specifically approved for the substance/product. Keep/Store only in original container. Keep container tightly closed.

##### **Hints on joint storage**

Keep away from:

##### **Further information on storage conditions**

Keep only in the original container in a cool, well-ventilated place. Store in a place accessible by authorized persons only. Handle and open container with care.

#### **7.3 Specific end use(s)**

Observe instructions for use. The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

### **SECTION 8: Exposure controls/personal protection**

#### **8.1 Control parameters**

Occupational exposure limits, UK (EH40/ed.2020): None

Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

Occupational exposure limit values, Ireland (2024): None

**DNEL/DMEL**

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6

Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Long-term
Limit value :	12,25 mg/m <sup>3</sup>
Limit value type :	DNEL worker (systemic)
Exposure route :	Inhalation
Exposure frequency :	Short-term
Limit value :	12,25 mg/m <sup>3</sup>

**8.2 Exposure controls**

**Appropriate engineering controls:** None particular.

**Personal protection equipment**



**Eye/face protection**

Suitable eye protection  
Use safety goggles (EN ISO 16321-1).

**Skin protection**

**Hand protection**

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Wear cotton under mitten if possible.

**Suitable gloves type :** Disposable gloves.

**Suitable material :** NBR (Nitrile rubber)

**Required properties :** liquid-tight.

**Breakthrough time :** > 60 minutes

**Thickness of the glove material :** > 0.5 mm

**Recommended glove articles :** EN 374

**Additional hand protection measures :** Do not wear gloves near rotary machines and tools. Check leak tightness/impermeability prior to use. Wear cotton under mitten if possible. Use gloves only once. Take recovery periods for skin regeneration.

**Remark :** For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Observe the wear time limits as specified by the manufacturer. Breakthrough times and swelling properties of the material must be taken into consideration. In the case of wanting to use the gloves again, clean them before taking off and air them well. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Barrier creams are not substitutes for body protection.

**Body protection**

**Remark :** Body protection: not required.

**Respiratory protection**

exceeding exposure limit values

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

**Suitable respiratory protection apparatus**

Combination filtering device Filtering device (EN 147) Full-/half-/quarter-face masks (EN 136/140) Filtering Half-face mask (EN 149) Particle filter device (EN 143).

Filtering device (full mask or mouthpiece) with filter: A P

**Additional measures for respiratory protection**

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m<sup>3</sup> (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m<sup>3</sup> (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 10000 mL/m<sup>3</sup> (1.0 % by vol.) Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo. Full-face mask or mouthpiece with particulate filter: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 15 times the exposure limit. P3 filter: up to a max. of

### Remark

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

### General information

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Immediately remove any contaminated clothing, shoes or stockings.

### Other protection measures

Further information: see technical data sheet.

Further information: see technical data sheet.

Further information: see technical data sheet.

Technical measures and the application of suitable work processes have priority over personal protection equipment. See section 7. No additional measures necessary.

### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance :  
Physical state: paste  
Colour: grey  
Odour: characteristic

### Safety characteristics

Flash point :	>	100 °C	DIN 53213-1
Evaporation rate :	<	1	
Vapour pressure :	( 50 °C )	<	1000 hPa
Relative density :	( 20 °C )		g/cm <sup>3</sup> DIN 53217
Viscosity :	( 20 °C )	approx.	900 mPa*s
Melting point/freezing point :	not applicable		
Initial boiling point and boiling range :	No data available		
Decomposition temperature :	No data available		
Auto-ignition temperature :	No data available		
Flammable gases :	Not applicable.		
Flammable solids :	Not applicable.		
Oxidising properties.	No data available.		
Lower explosion limit :	No data available		
Upper explosion limit :	No data available		
Explosive properties :	No data available.		
Relative vapour density :	No data available		
Water solubility :	practically insoluble		
Partition coefficient n-octanol/water :	No data available		
pH :	No data available		
Flow time :	not determined		
Kinematic viscosity :	No data available		
Odour threshold :	No data available		
Particle characteristics:	No data available		

### 9.2 Other information

None

Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

### 10.4 Conditions to avoid

Ignition hazard.

### 10.5 Incompatible materials

No information available.

### 10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

#### Acute toxicity:

Based on available data, the classification criteria are not met.

##### Acute oral toxicity

Parameter :	LD50 ( 2,2-BIS-(4-(2,3-EPOXYPROPOXY) PHENYL) PROPANE, POLYMER ; CAS No. : 25085-99-8 )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 5000 mg/kg
Parameter :	LD50 ( QUARTZ (SIO2) ; CAS No. : 14808-60-7 )
Exposure route :	Oral
Effective dose :	500 mg/kg
Parameter :	LC50 ( REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6 )
Exposure route :	Oral
Species :	Rat
Effective dose :	30000 mg/kg

##### Acute dermal toxicity

Parameter :	LD50 ( 2,2-BIS-(4-(2,3-EPOXYPROPOXY) PHENYL) PROPANE, POLYMER ; CAS No. : 25085-99-8 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	20000 mg/kg
Parameter :	LC50 ( REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6 )
Exposure route :	Dermal
Species :	Rat
Effective dose :	> 2000 mg/kg

**Skin corrosion/irritation:** Skin Irrit. 2;H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

**Serious eye damage/irritation:** Eye Irrit. 2;H319 - Serious eye damage/eye irritation : Category 2 ; Causes serious eye irritation.

**Respiratory or skin sensitisation:** Skin Sens. 1;H317 May cause an allergic skin reaction.

Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. Risk of serious damage to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

#### Skin sensitisation

Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

Parameter :	Skin sensitisation ( REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6 )
Species :	Guinea pig
Effective dose :	50 %
Result :	Strong sensitising.
Method :	OECD 406
<b>Germ cell mutagenicity:</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity:</b>	Based on available data, the classification criteria are not met.
<b>Reproductive toxicity:</b>	Based on available data, the classification criteria are not met.
<b>STOT-single exposure:</b>	Based on available data, the classification criteria are not met.
<b>STOT-repeated exposure:</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard:</b>	Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

No information available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter :	LC50 ( REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6 )
Species :	Fish
Effective dose :	1,3 mg/l
Exposure time :	96 h
Method :	OECD 203

##### Acute (short-term) toxicity to algae and cyanobacteria

Parameter :	EC50 ( 2,2-BIS-(4-(2,3-EPOXYPROPOXY) PHENYL) PROPANE, POLYMER ; CAS No. : 25085-99-8 )
Species :	Daphnia magna (Big water flea)
Effective dose :	1,4 mg/l
Exposure time :	48 h
Parameter :	EC50 ( 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL ; CAS No. : 90-72-2 )
Species :	Daphnia magna (Big water flea)
Effective dose :	41,3 mg/l
Exposure time :	48 h
Parameter :	EC50 ( 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL ; CAS No. : 90-72-2 )
Species :	Algae
Evaluation parameter :	Acute (short-term) toxicity to algae and cyanobacteria
Effective dose :	84 mg/l
Exposure time :	72 h

### 12.2 Persistence and degradability

#### Biodegradation

Parameter :	Biodegradation ( QUARTZ (SiO2) ; CAS No. : 14808-60-7 )
Inoculum :	Biodegradation
Degradation rate :	-
Parameter :	Biodegradation ( REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700) ; CAS No. : 25068-38-6 )
Inoculum :	Biodegradation
Degradation rate :	12 %
Test duration :	28
Evaluation :	Not readily biodegradable (according to OECD criteria)



# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

Method : OECD 301B

### 12.3 Bioaccumulative potential

No information available.

### 12.4 Mobility in soil

No information available.

### 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to Regulation 2023/707.

### 12.6 Endocrine disrupting properties

No information available.

### 12.7 Other adverse effects

No information available.

### Additional ecotoxicological information

The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3). Do not allow to enter into surface water or drains.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Disposal should be according to local, state or national legislation. Dispose through authority facilities or pass to a chemical disposal company.

**EWC-Code:** 08 04 09 (product itself) and 15 02 02 (Paper, inert material, etc. contaminated with the product)

## SECTION 14: Transport information

### 14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

### 14.4 Packing group

No dangerous good in sense of these transport regulations.

### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

### 14.6 Special precautions for user

None

### 14.7 Maritime transport in bulk according to IMO instruments:

Not relevant.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

Must not be used by persons under 18 years of age.

#### Authorisations and/or restrictions on use

##### Restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

None relevant.

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

### National regulations

MAL code number according to Executive Order no. 301 from 13 May 1993 on the determination of code numbers (The Danish Working Environment Service): 00-5

PR-Number (Danish): 1404817

### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes

Section 1-16 (general update).

### Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road  
ASTM = American Society of Testing and Materials (US)  
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)  
DNEL = Derived No-Effect Level  
DT50 = Time for 50% loss; half-life  
EbC50 = Median effective concentration (biomass, e.g. of algae)  
EC50 = Median effective concentration  
EINECS = European Inventory of Existing Commercial Chemical Substances  
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)  
ErC50 = Median effective concentration (growth rate, e.g. of algae)  
EWC = European Waste Catalogue  
IATA = International Air Transport Association  
IC50 = Concentration that produces 50% inhibition  
IMDG = International Maritime Dangerous Goods Code  
IMO = International Maritime Organization  
LC50 = Concentration required to kill 50% of test organisms  
LD50 = Dose required to kill 50% of test organisms  
LEL = Lower Explosive Limit/Lower Explosion Limit  
LOAEL = Lowest observed adverse effect level  
MRL = Maximum Residue Limit  
NOAEL = No Observed Adverse Effect Level  
NOEC = No observed effect concentration  
NOEL = No Observable Effect Level  
OEL = Occupational Exposure Limits  
PBT = Persistent, Bioaccumulative or Toxic  
PNEC = Previsible Non Effect Concentration  
STEL = Short-Term Exposure Limit  
TWA = Time-Weighted Average  
vPvB = Very Persistent and Very Bioaccumulative

### Key literature references and sources for data

ECHA: REACH Registration dossier from ECHA's web page.

### Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

### Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : WENCON PUTTY  
Revision date : 19.06.2025  
Print date : 19-06-2025

Version : 8.0.0 (7.0.0)

---

H411 Toxic to aquatic life with long lasting effects.

**Training advice**

The regulations of the national employment safety and employment protection commission about the handling for polyurethane/epoxy have to be observed.

**Additional information**

This safety data sheet contains more than one ES in an integrated form. Contents of the exposure scenarios have been included into sections 1.2, 3, 8, 9, 11, 12, 13, 14, 15 and 16 of this safety data sheet.

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---