

TEMPORARY REPAIRS & MAINTENANCE

Optimize your efficiency and safety onboard with swift and effective repair kits at sea



SUITABLE FOR:

- Cable Pipe
- Cargo Pipe
- HYD return line
- HT & LT Cooling pipe
- Heating Coils
- IGG Pipe
- MGO Pipe
- SW Pipe
- SW Strainer housing
- Scrubber Pipe (GRE)
- Sludge Pipe
- Steam Pipe to 7 bars

IMPA No.	Kit name	Description	Product No.
812341	Steel Pipe/ Plate & GRE Repair	Pipe from DN 6–250, 2.5 m ²	8750
812331	Steel Pipe Repair 1	Pipe from DN 150–250, 1.4 m ²	8751
812332	Steel Pipe Repair 2	Pipe from DN <150, 1.4 m ²	8752
812333	GRE Pipe Repair	DN 250–750, 6,2 m ²	8753
812326	SW Strainer/Filter Housing Rep	Up to 3,6 m ² of plate	8754

APPROVED BY



NON-DANGEROUS GOODS



<div style="text-align: right;">Kit name</div> <div style="text-align: left;">Repair examples</div>	Steel Pipe/Plate & GRE Repair	Steel Pipe Repair 1 Ø 150–250 mm	Steel Pipe Repair 2 < Ø 150 mm	GRE Pipe Repair Ø <250–750 mm	SW Strainer/Filter Housing Rep
	IMPA No: 812341 Product No: 8750	IMPA No: 812331 Product No: 8751	IMPA No: 812332 Product No: 8752	IMPA No: 812333 Product No: 8753	IMPA No: 812326 Product No: 8754
Steel pipe DN 32, repair length 300 mm. With Putty, Rapid and 3 layers of Reinforcement tape (0,05x10m)	16 pcs	16 pcs	8 pcs		
Steel pipe DN 100, repair length 300 mm. With Putty, Rapid and 3 layers of Reinforcement tape (0,05x10m)	6 pcs	6 pcs	3 pcs		
Steel pipe DN 150, repair length 300 mm. With Putty, Cream and 3 layers of Reinforcement tape (0,05x10m)	2 pcs	4 pcs			
Steel pipe DN 250, repair length 300 mm. With Putty, Cream and 3 layers of Reinforcement tape (0,05x10m)	1 pcs	2 pcs			
Steel pipe DN 32, Ø5mm damage. Repair length 105 mm. With Putty and Pipe tape 0,05 x 1,5 m	5 pcs		2 pcs		
Steel pipe DN 100, Ø5mm damage. Repair length 105 mm. With Putty and Pipe tape 0,05 x 1,5 m	1 pcs		3 pcs		
Steel pipe DN 150, Ø5mm damage. Repair length 105 mm. With Putty and Pipe tape 0,05 x 3,5 m	2 pcs	2 pcs			
Steel pipe DN 200, Ø5mm damage. Repair length 105 mm. With Putty and Pipe tape 0,1 x 3,5 m	1 pcs	1 pcs			
Heating coils DN 50, repair length 1600 mm. Hi-Temp coating and 3 layers of Reinforcement tape (0,05x10m)	1 pcs		1 pcs		
FW HT pipe with Hi-Temp coating	✓		✓		
GRE pipe DN 125, repair length 500 mm. With UW coating and 3 layers of Reinforcement tape (0,05x10m)	1 pcs			7 pcs	
GRE pipe DN 750, repair length 500 mm. With UW coating and 3 layers of Reinforcement tape (0,05x10m)				1 pcs	
Repair of SW strainer/filter housing, with Cream and Coating	1.2 m ²	2.0 m ²	1.0 m ²		3.0 m ²
Pump well with UW cream and UW coating, 2 layers of 500 µ each	0.44 m ²				
Repair of cracked paint under water or at oil-polluted surfaces. UW coating, 2 layers of 500 µ each	0.44 m ²			3.1 m ²	
Putty 5000 µ (for repair of penetrated holes)	0.1 m ²	0.1 m ²	0.1 m ²		0.1 m ²
Cream 2000 µ (for building up surface)	0.3 m ²	0.9 m ²			0.9 m ²
Coating White (first layer of coating)	2.0 m ²	2.0 m ²	1.0 m ²		3.0 m ²
Coating Blue (second layer of coating)	2.0 m ²	2.0 m ²	1.0 m ²		3.0 m ²