

NB! Read Instructions For Use sheet before use

# Wencon Pipe Repair Kit

Fast curing pipe repair kit, made for quick and effective repairs of cracks, leaks, fractures and corrosion porosity in pipings. No tools needed. Suitable for all pipes and surfaces.



- Designed for maritime use & Product Type Approved – Your safeguard when pipes fail
- Proven and reliable – Tested in lab, fieldproven through decades
- 10–30 min. curing time – Less downtime

## General information

Wencon Putty and Pipe Tape form a powerful duo for quick and durable repairs of corroded and damaged metal surfaces.

Wencon Putty is a fast-curing, two-component epoxy in a practical stick format, easy to apply directly to the affected area. It bonds strongly to all metals, is non-conductive, and resists oil, water, salt water, most diluted acids, and temperatures up to 250°C.

Wencon Pipe Tape is a pre-impregnated fibreglass tape with a flexible, knitted structure that ensures high strength and easy application, even on irregular shapes like elbows, joints, and fittings.

## Application

Both products are widely used for emergency repairs where quick curing and strong bonding are essential. Typical application areas include sealing, filling cracks, stopping leakages and holes in pipes, flanges, tanks, and other equipment carrying water, oil, steam, most gases, and various solvents.

## Customer Benefits

### Wencon Putty

- Cures in 10–20 minutes
- Simple apply procedure with cut and knead
- Fill out and seal cracks, leaks and holes
- Strong adhesion to all metal surfaces
- Fully machinable

### Wencon Pipe Tape

- Quick and effective to use
- No mixing – No tools
- Water activated
- Ready for use in 10 seconds
- Cures in 10–30 minutes
- Suitable for all pipes and surfaces

NB! Read Instructions For Use sheet before use

**Pipe Tape usage chart**

Check below chart for needed pipe tape based on pipe diameter.



Outer Pipe Diameter	Pipe Wrap Length	9 x Wraps	Wencon Pipe Tape Quantity (rolls)	Wencon Pipe Tape Quantity (rolls)
mm	mm	mm	5cm x 150cm	5cm x 350cm
15	47	423	One	
20	63	567	One	
25	79	707	One	
32	101	905	One	
40	126	1131	One	
50	157	1414	One	
80	251	2262	Two	One
100	314	2828	Two	One
125	393	3535		One
150	471	4242		Two
200	628	5656		Two
250	786	7070		Two
300	943	8483		Three

**Pipe pressure with Wencon Putty: 50 Bar (725 p.s.i.)\***

The solution has been tested on pipes with an outer diameter of 60.3 mm (DN50) and 114.3 mm (DN100) using a Ø5 mm hole.

While the product has been certified for safe use up to 50 bar, actual test results have shown significantly higher pressure resistance. When applied according to the guidelines, pipes with smaller diameters are also expected to withstand 50 bar under the same conditions.

Scan for website


**Product numbers:**

No. 1047 Wencon Pipe Repair Kit, 2 units/(5cm x150cm) (2x60 inch) + putty (125gr) N/A

No. 1048 Wencon Pipe Repair Kit, 5 units/(5cm x150cm) (2x60 inch)+ putty (125gr) N/A

**IMPA no.**
**ISSA no.**